

DATASHEET - PV-400ANH3



Fuse-link, high speed, 400 A, DC 1000 V, NH3, gPV, UL PV, UL, IEC, dual indicator



Catalog No. PV-400ANH3

Similar to illustration

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	400
Rated voltage			DC 1000 V
Construction size			NH3
Utilization category			gPV UL PV
Status indicator			dual indicator
Description			live gripping lugs
Breaking Capacity		kA	50
usable for size/applications			protection of photovoltaic array combiners and disconnects
Standard/Approval			UL IEC
Shape			square-body with knife blade contacts
Standards/Regulations			UL 2579 IEC 60269-6
Optional accessories			fuse-holder SD3-D-PV

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecI@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			NH3
Rated current		A	400
Rated voltage		V	1000
Voltage type			DC
Rated switching capacity		kA	50
Utilization category			gPV (photovoltaic protection)
Type of fuse status indicator			Combination fuse status indicator
Insulated metal gripping lugs (IMGL)			No

Assets (links)

Declaration of CE Conformity

00003223