

DATASHEET - FUSE 1600A 690V 4BKN/65 AR UC



Fuse-link, high speed, 1600 A, AC 690 V, 200 kA, size 4, 105 x 120 x 67 mm, aR, IEC, UL, type K indicator



Part no. FUSE 1600A 690V 4BKN/65 AR UC
Catalog No. 170M7081

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	1600
Rated voltage			AC 690 V
Construction size			size 4
Size			105 x 120 x 67 mm
Utilization category			aR
Status indicator			type K indicator
Breaking Capacity		kA	200
usable for size/applications			semiconductor protection
Standard/Approval			IEC UL
Shape			square body with flush end contacts
Standards/Regulations			IEC 60269-4

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])			
Fuse construction type according to IEC 60269			4
Type of current			AC
Rated voltage AC		V	690
Rated voltage DC		V	
Rated current		A	1600
Utilization category			aR (accompanied semiconductor protection)
Breaking capacity		kA	200
Colour code			None
Type of fuse status indicator			Other
Power loss at rated current		W	220
Mounting holes			M10
Centre-to-centre distance of connections		mm	66.6

Additional product information (links)

Product datasheet (pdf)	http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-b/Bus_Ele_DS_720020_170M.pdf
-------------------------	---