



**Fuse-link, LV, 400 A, AC 500 V, NH2, aM, IEC, dual indicator, live gripping lugs**

**Catalog No. 400NHM2B**

Similar to illustration

## Delivery program

|                       |   |    |                                                      |
|-----------------------|---|----|------------------------------------------------------|
| Product range         |   |    | Fuse                                                 |
| Basic function        |   |    | Fuse-link                                            |
| Field of application  |   |    | low voltage                                          |
| Rated current         | I | A  | 400                                                  |
| Rated voltage         |   |    | AC 500 V                                             |
| Construction size     |   |    | NH2                                                  |
| Utilization category  |   |    | aM                                                   |
| Status indicator      |   |    | dual (combination) indicator system                  |
| Description           |   |    | live gripping lugs                                   |
| Breaking Capacity     |   | kA | 120                                                  |
| Standard/Approval     |   |    | IEC                                                  |
| Shape                 |   |    | square body with knife blade contacts                |
| Standards/Regulations |   |    | IEC 60269-2 fuse system A<br>DIN 43620<br>VDE 0636-2 |

## Technical data ETIM 7.0

|                                                                                                                                                                                     |  |    |                                   |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|----|-----------------------------------|
| Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)                                                                                                             |  |    |                                   |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015]) |  |    |                                   |
| Construction size                                                                                                                                                                   |  |    | NH2                               |
| Rated current                                                                                                                                                                       |  | A  | 400                               |
| Rated voltage                                                                                                                                                                       |  | V  | 500                               |
| Voltage type                                                                                                                                                                        |  |    | AC                                |
| Rated switching capacity                                                                                                                                                            |  | kA | 120                               |
| Utilization category                                                                                                                                                                |  |    | aM (switchgear protection)        |
| Type of fuse status indicator                                                                                                                                                       |  |    | Combination fuse status indicator |
| Insulated metal gripping lugs (IMGL)                                                                                                                                                |  |    | No                                |